

DCT Delta FOSTR-A-F

FOSTR-A-F MICRORECEIVER FOR FIBRE NODES AND AMPLIFIERS



- FSK Microreceiver in operation with HEC 1004 and DELTANET NMS software acc. EN 60728-14
- Pluggable module for: ONH, ONB, BKD, LHD, NVD Typen (latest generation)
- RX frequency 868.3 MHz
- Monitoring status LED for displaying operation mode
- Monitoring functions: DS ON/OFF, burst mode ON/OFF, Ingress detection switch 0 / 6 / 45 dB
- Intelligent integration into DELTANET via Smartphone application
- Very low power consumption and cost effective solution for monitoring your network

SPECIFICATIONS	
Application	ONH, ONB, BKD, LHD, NVD Types (Latest Generation)
RX Frequency	868,3 MHz (other Frequencies on request)
Monitoring Status LED	green: 0 / 6 / 45 dB, DS ON/OFF, Burst Mode ON/OFF
Bandwidth	200 kHz
Spurious	< 10dBµV
Dynamic Input Level	30..75 dBµV
Data Speed	9600 Bps
Local Interface	RS-232
Power Supply	6-24 V / < 0,4W@24V / < 0.18W@12 V
Dimensions	25 x 24 x 8 mm
Weight	0.02 kg