

OMT / Depolarizer



Ku-Band OMT (Ortho Mode Transducer)



Shown with 90° bend fitted

Swedish Microwave's OMT is used to separate two orthogonal linearly polarized signals simultaneously.

The OMT can also support circular polarizations with a depolarizer.

Greater than 31.5 dB isolation between the two linear polarizations is achieved.

Accessories:


- Bend for the vertical polarization.
- Waveguide cover for H-pol port.
- Depolarizer for circular polarizations.

TECHNICAL SPECIFICATIONS


MODEL:	OMT Ku-Band
Frequency Range Vertical	10.70 - 14.50 GHz
Frequency Range Horizontal	10.70 - 12.75 GHz
Input Waveguide	C120 (circular 18 mm)
Output Waveguides	WR75
Input VSWR	1.5:1 max
Cross Polarization (isolation)	31.5 dB min.
Transmission Loss	0.1 dB
Temperature Range	Storage and operating: - 40° to + 80° C
Weight	200 g
Material	Zinc
Dimensions	125 x 48 x 46 mm, (73 x 48 x 45 mm w/o bend), for drawing, see www.smw.se

Rev.11-20-2B

Depolarizer (Circular to linear polarization)



RHC @ Vertical output
LHC @ Horizontal output



LHC @ Vertical output
RHC @ Horizontal output

TECHNICAL SPECIFICATIONS

MODEL:	Depolarizer LHC & RHC Ku-Band
Polarization	Circular LHC & RHC together with SMW Twin/OMT
Frequency Range	10.70 - 12.75 GHz
VSWR	1.25:1 typ.
Transmission Loss	0.1 dB typ.
Cross Polarization Rejection	20 dB typ.
Waveguide	C120 (circular waveguide 18 mm)
Material	Aluminium (black anodized)
Temperature Range	Storage and operating: - 40° to + 80° C
Weight	90 g
Dimensions	L = 47 mm, Ø 50 mm, for drawing, see www.smw.se

Rev.11-20-2B

Above parameters are generic product family values. For part number specific min./max. values, please consult us.

Specifications are subject to change without notice. Products from Swedish Microwave AB are made for commercial use.

Swedish Microwave AB, Dynamov. 5, S-591 61 Motala, Sweden. Tel: +46 141 216135, sales@smw.se, www.smw.se