

## COMMSCOPE Aluminium Cable 750 Series

750 JCA		
Trunk & Distribution cable without flooding compound		
Center conductor Ø	4,24 mm	Center conductor
Dielectric Ø	17,22 mm	Dielectric
Jacket Ø	20,83 mm	Solid aluminium pipe
Shielding (dB)	> 120 dB	
Velocity of propagation	0,87	
Minimum Bend radius	20,30 cm	
Maximum tensile strength	306 kg	
Frequency (MHz)	dB/100 m	PE Jacket
5	0,36	
211	2,43	
450	3,67	
600	4,30	
750	4,86	
1000	5,71	
2000	8,31	



750 JCASS		
Trunk & Distribution cable with flooding compound		
Center conductor Ø	4,24 mm	Center conductor
Dielectric Ø	17,22 mm	Dielectric
Jacket Ø	20,08 mm	Solid aluminium pipe
Shielding (dB)	> 120 dB	
Velocity of propagation	0,87	
Minimum Bend radius	20,30 cm	MigraHeal™
Maximum tensile strength	306 kg	Flooding compound
Frequency (MHz)	dB/100 m	PE Jacket
5	0,36	
211	2,43	
450	3,67	
600	4,30	
750	4,86	
1000	5,71	
2000	8,31	

