

MWTM Shrinking Tubes

Shrinking Tubes for Electrical Isolation, for Sealing and Protection against Corrosion



SPECIFICATIONS				
Temperature Range	-40°C bis +120°C (uncoated) -40°C bis + 90°C (coated)			
Dielectrical strength	14 kV/mm			
Color	black			
Availability	A/U = coil, /172 1m / cut in 1m; with flooding compound			
ORDER NUMBER	DIMENSIONS (MM)			
	H		W	
	a (min.)	b (max.)	a (min.)	b (min.)
MWTM 10/ 3-A/U MWTM 10/ 3-1000/172	10,0	3,0	0,3	0,9
MWTM 16/ 5-A/U MWTM 16/ 5-1000/172	16,0	5,0	0,3	1,4
MWTM 25/ 8-A/U MWTM 25/ 8-1000/172	25,0	8,0	0,4	2,0
MWTM 35/12-A/U MWTM 35/12-1000/172	35,0	12,0	0,4	2,0
MWTM 50/16-A/U MWTM 50/16-1000/172	50,0	16,0	0,5	2,0
MWTM 63/19-A/U MWTM 63/19-1000/172	63,0	19,0	0,6	2,4
MWTM 75/22-A/U MWTM 75/22-1000/172	75,0	22,0	0,6	2,7
MWTM 85/25-1000/U MWTM 85/25-1000/172	85,0	25,0	0,6	2,8
MWTM 95/29-1000/U MWTM 95/29-1000/172	95,0	29,0	0,7	3,1
MWTM 115/34-1000/U MWTM 115/34-1000/172	115,0	34,0	0,7	3,1
MWTM 140/42-1000/U MWTM 140/42-1000/172	140,0	42,0	0,7	3,1
MWTM 160/50-1000/U MWTM 160/50-1000/172	160,0	50,0	0,7	3,1
MWTM 180/60-1000/U MWTM 180/60-1000/172	180,0	60,0	0,7	3,1

