








Hardline Adapters

All versions with PIN:
PIN-Standard length 47 mm
PIN-Diameter 1,8 mm

TYPE	
5/8 M-5/8 M 5/8 Male → 5/8 Male	
5/8M-3,5/12F 5/8 Male → 3,5/12 Female	
5/8M-IEC14F 5/8 Male → IEC Female	
5/8M-FF HQ PCT 625 F CH 5/8 Male → F Female	
5/8M R75 Terminator 75 Ohm for 5/8	
5/8F-5/8F G KS KS F 5/8 Female → 5/8 Female	
5/8F-PG11M 5/8 Female → PG11 Male	
G CH AFM 5/8 Female → F Male	
5/8F-FF 5/8 Female → F Female	
5/8M-PG 11F 5/8 Male → PG 11 Female	

3,5/12M-5/8F 3,5/12 Male → 5/8 Female	
3,5/12M-IEC14F 3,5/12 Male → IEC Female	
3,5/12M-FF 3,5/12 Male → F Female	
3,5/12M R75 Terminator 75 Ohm for 3,5/12	
3,5/12F-3,5/12F 3,5/12 Female → 3,5/12 Female	
PG 11M-3,5/12F PG11 Male → 3,5/12 Female	
PG 11M-IEC 14F PG 11 Male → IEC Female with M14 external thread	
PG11M-FF PG11 Male → F Female	
PG 11 M-5/8 F PG 11 Male → 5/8 Female	
IEC14M-IEC14M IEC Male → IEC Male	
IEC 14M-FF IEC Male → F Female	
IEC 14M R75 Terminator 75 Ohm for IEC	
IEC14F-IEC14F IEC Female → IEC Female	

IEC14F-FF IEC Female → F Female	
GP 90 T 90° Connector with 5/8 Pin	
GSPB TSPB 5/8 Splice Block	
5/8M-FF 5/8 Male → F Female	
5/8M-AC 5/8 Male → AC	
XX-SPR Splice reducer	
PG11M AC 47MM PG 11 Male → AC	

Other product types on request.