









PPC Compression Connectors

UNIVERSAL COMPRESSION CONNECTORS, (RG 59)		F PLUG COMPRESSION, WEATHERPROOF, IP 67, DIELECTRIC 2,7MM	
EX 59 HE		CMP MC 30	
UNIVERSAL COMPRESSION CONNECTORS, (RG 11), FOR DIELECTRIC 7,2 MM		AQUATIGHT® EX® CONNECTOR, INTEGRATED PORT SEAL, EXTENDED BODY, (RG 6)	
EX 11		EX 6 XL WS	
F PLUG COMPRESSION (RG 6), FOR DIELECTRIC 4.6 MM, WITH CONTACT SPRING		F PLUG COMPRESSION (RG 6), FOR DIELECTRIC 4.6 MM	
EX 6 NTPLUS		EX 6-49/83	
MINI COAX F PLUG COMPRESSION, FOR DIELECTRIC 4.8 MM		COMPRESSION MALE CONNECTOR IEC – RG6	
EX 6-51/83		EX 6-49/83 IECM	
MINI COAX F PLUG COMPRESSION			
EX 6-49/83 IECF			

SPECIFICATIONS

- Weatherproof, IP 67
- Bandwidth 0 MHz to 3 GHz
- Impedance 75 Ohms (nominal)
- Return Loss Minimum -30 dB to 3 GHz
- Insertion Loss Less than 0.10 dB to 3 GHz
- Operating Voltage 90 V (at 60 Hz continuous AC)
- Operating Temperature -40o F to + 140o F (-40o C to 60o C)
- Cable Retention 45 lbs (20.41 kg) minimum

Other product types on request.