



FEEL THE WONDER

ACCESS CABLE GATEWAY

MARLIN L CGA4236

Dual-Band Wi-Fi 6

Smart Ultra-Broadband Cable Gateway with Voice for above Gigabit Speeds



The MARLIN L CGA4236 is a DOCSIS® 3.1 capable cable gateway offering triple-play services beyond Gigabit speeds, while providing VoIP functions for residential and business users. The CGA4236 is equipped with the latest Wi-Fi 6 technology, allowing for faster throughputs, better performance in dense multi-user environments and saving battery lifetime of the connected devices. The CGA4236 has been designed to cover all regional requirements for Europe, Latin America and North America.

Highest Performance with DOCSIS 3.1

The CGA4236 matches perfectly with the requirements of cable operators willing to propose ultimate Broadband access to their customers.

The CGA4236 cable gateway is fully compliant with the latest DOCSIS 3.1 specification as published by CableLabs® and is capable of delivering downstream cable speeds of up to 3.6 Gbps by using 2 Orthogonal Frequency-Division Multiplexing (OFDM) downstream channels (and up to 5 Gbps in case of 2 OFDM plus 32 Single Carrier QAM) and up to 1.5 Gbps upstream by using 2 Orthogonal Frequency-Division Multiple Access (OFDMA) upstream channels.

This enhanced and superior performance allows cable operators to propose multi-Gigabit data services to their customers through various applications, from IP connectivity to ultra-high speed internet access and gaming.

Wi-Fi 6 Technology

Wi-Fi 6 – a stronger and more performing wireless connectivity – is a major evolution that improves gigabit-services delivery through providing reliable connections to a large number of devices in several ways. This evolution is intended for both 2.4 and 5 GHz, making Wi-Fi 6 the first major upgrade for Wi-Fi at 2.4 GHz since Wi-Fi 4 in 2009. While it keeps the data rate the same as Wi-Fi 5, Wi-Fi 6 increases signal robustness to accommodate more devices and allow better sharing of the wireless channel.

Wi-Fi 6 provides higher maximum data rate on the network by using higher orders of modulation for more data – up to 1024 QAM from Wi-Fi 5's 256 QAM. It lowers latency by dramatically reducing delay times as data is sent, improving load times and helping avoid disconnects and other issues. This is particularly helpful for online gaming for example. Additionally, Wi-Fi 6 provides a mechanism to reduce interference between neighboring routers through efficient spectrum use, improving service quality levels to customers that live in high Wi-Fi density areas. Finally, Wi-Fi 6 introduces a concept called Target Wake Time (TWT), allowing the access point to put clients' Wi-Fi radio in a sleep mode until it's needed, meaning power savings and longer battery life.

Features at a Glance

- DOCSIS® 3.1 compliant
- Backward compatible with DOCSIS®/EuroDOCSIS® 3.0
- 2 x 2 OFDM(A) bonded channels in DOCSIS 3.1 mode
- 32 x 8 bonded channels in DOCSIS/EuroDOCSIS 3.0 mode
- Automatic switchable diplexer for up- and downstream
- Up to 1.2 GHz full band capture tuner
- Built in RF spectrum analyzer
- 4 GE LAN ports
(1 2.5 Gigabit Ethernet and 3 GE LAN ports optional)
- Dual-band concurrent Wi-Fi (with high power optional)
 - 2.4 GHz (3x3) Wi-Fi 6 (IEEE 802.11ax)
 - 5 GHz (4x4) Wi-Fi 6 (IEEE 802.11ax)
- Enabled to support Wireless XL™ (sold separately)
- Hotspot GRE, Passpoint™
- 2 FXS ports for phone or fax
- Voice (Euro)PacketCable™ 2.0 & 1.5 and SIP compliant
- 1 superspeed USB 3.1 Gen 1 master port
- MoCA 2.0 (optional)
- Future-proof Added Value Services platform supporting Technicolor RDK-B (Reference Design Kit - for Broadband)
- SNMP and TR-069 remote management
- Dual stack IPv4 and IPv6 DS-Lite enabled
- Managed external battery backup unit (optional)



ACCESS CABLE GATEWAY

MARLIN LCGA4236

Next-Gen Wi-Fi 6 and Technicolor Wi-Fi XL

Featuring the next-generation Wi-Fi 6 technology on both the 2.4 GHz and 5 GHz bands, the CGA4236 makes optimal use of the radio spectrum allowing for faster throughputs, better performance in dense multi-user environments and saving battery lifetime of the connected devices. With its optimized antenna configuration, the CGA4236 enables a best in class coverage.

The CGA4236 supports Wi-Fi XL™, a differentiated Wi-Fi solution that delivers multi-user gigabit Wi-Fi services throughout the home.

RDK-B Open Source Software

With the growth of consumer devices connected to internet, the rise of streaming video and the Internet of Things (IoT), Service Providers (SPs) need to quickly adapt to provide faster and more reliable home networks.

The Reference Design Kit for Broadband (RDK-B) is an open source initiative standardizing software functionalities in broadband devices for SPs to efficiently deploy services to a large customer base.

RDK-B provides all needed features to manage complex broadband functions such as Wide Area Networking (WAN), Local Area Networking (LAN), data reporting & management, and home-networking technologies, such as Wi-Fi and Multimedia over Coax Alliance (MoCA).

Based on Cisco's Common Component Software Platform now owned by Technicolor, RDK-B is a fully modular, portable and customizable software solution that is currently running on 5+ million broadband gateways.

Advanced Security

The integrated firewall provides Stateful Packet Inspection (SPI), and an integrated Intrusion Detection and Prevention System (IDS) engine which monitors a wide range of attack patterns, and logs potential security breaches to a local cache or remote server.

To secure data exchange between the gateway and the cable operators' servers, BPI+ communications privacy is used.

The CGA4236 also supports powerful wireless security mechanisms, such as Wi-Fi Protected Access (WPA, WPA2 and WPA3) together with a secure and user friendly connection and configuration mechanism for connecting wireless clients (WPS).

In addition, the CGA4236 supports multiple wireless networks (mSSID) per Wi-Fi radio enabling to set up independent virtual wireless access points, including controlled wireless hotspots. These additional wireless networks allow other wireless users to enjoy high-performance access without any compromise on the integrity of the basic network, thus keeping the original network access limited and secure.

Voice Performance

The CGA4236 is (Euro)PacketCable 2.0 and (Euro)PacketCable 1.5 compliant and can operate in MGCP as well as SIP mode.

The CGA4236 supports all standard codecs (optionally also including iLBC and BV16) and is equipped with basic and extended CLASS features such as caller ID and call waiting. Gateway and voice operations support data throughput and complex voice calls simultaneously.

Superspeed USB

The CGA4236 comes with superspeed USB 3.1 Gen 1 master ports to support devices such as mass storage devices, enabling transfer speeds multiple times higher than the conventional USB 2.0 and with more power output.

Easy to Manage

The CGA4236 is completely designed according to the TR-069's TR-098 IGD data model through which the device can be configured remotely by the operator without interrupting the end user's experience.

In addition, the TR-181i2 Device:2 data model is made available to further increase the remote management capabilities towards life cycle management, diagnostics and application management.

MoCA (optional)

The CGA4236 also optionally includes an integrated MoCA 2.0 interface which enables the gateway to provide connectivity to set-top boxes and client devices connected within the home.

IPv6 Enabled

With the approaching IPv4 address pool depletion, cable gateway products need to be ready for IPv6. Technicolor is a frontrunner in the support of IPv6 on its devices, with the CGA4236 enabled for multiple IPv6 field scenarios.

Internet Protocol version 6 is the next generation of Internet technologies aiming to effectively support the ever-expanding Internet usage and functionality, and to address security concerns that exist in an IPv4 environment.

ACCESS CABLE GATEWAY

MARLIN LCGA4236

Technical Specifications

Hardware

■ CPU	Dual core ARMv7 and Viper CPUs (total 11700 DMIPs)
■ Interfaces WAN	1 F-Type RF connector, external threaded
■ Interfaces LAN	4-port autosensing Ethernet LAN switch, with: 4 x 10/100/1000 Base-T Ethernet 3 x 10/100/1000 Base-T and 1 x 10/100/1000/2500 Base-T (optional)
	1 Wi-Fi 6 (IEEE 802.11ax) 2.4 GHz radio 1 Wi-Fi 6 (IEEE 802.11ax) 5 GHz radio MoCA 2.0 for LAN through WAN RF connector (optional)
■ Interfaces other	2 FXS POTS ports 1 USB 3.1 Gen 1 master port 1 external Battery Backup Unit telemetry port (optional)
■ Power input	DC jack
■ Power supply	12 VDC external PSU
■ AC Voltage	100 - 240 VAC, 50 - 60 Hz (switched mode PSU)
■ Operating temperature	0 - 40 °C (32 - 104 °F)
■ Operating humidity	20 - 95 % RH non-condensing
■ Storage temperature	-20 - 70 °C (-4 - 158 °F)

Cable certifications

■ Data	DOCSIS® 3.1 Certified
■ Voice	(Euro)PacketCable™ 2.0 & 1.5 compliant
■ CMTS interoperability	Any qualified DOCSIS 3.1 CMTS Any qualified DOCSIS®/EuroDOCSIS® 3.0 CMTS

RF downstream

■ Downstream modulation	64, 256, 1024, 2048 and 4096 QAM
■ Downstream frequency range	, software selectable 108 - 1218 MHz or 258 - 1218 MHz
■ Number of downstream channels	DOCSIS 3.1 2 OFDM (Euro)DOCSIS 3.0 Up to 32 bonded
■ Maximum downstream rates	DOCSIS 3.1 Up to 3.6 Gbps Up to 5 Gbps with 32 SC-QAM DOCSIS 3.0 1372 Mbps (theoretical, 32 x 42.88 Mbps) EuroDOCSIS 3.0 1780 Mbps (theoretical, 32 x 55.62 Mbps)
■ Capture windows	1.2 GHz full band capture
■ Channel bandwidth	DOCSIS 3.1 192 MHz DOCSIS 3.0 6 MHz EuroDOCSIS 8 MHz
■ Input signal level range	-15 dBmV / + 15 dBmV
■ Input impedance	75 Ohm

RF upstream

■ Upstream modulation	QPSK 8, 16, 32, 64 and 128 QAM DOCSIS 3.1 Up to 4096 QAM
■ Upstream frequency range, software selectable	5 - 85 MHz or 5 - 204 MHz
■ Number of upstream channels	DOCSIS 3.1 2 OFDMA (Euro)DOCSIS 3.0 Up to 8 bonded
■ Maximum upstream rates	DOCSIS 3.1 Up to 1.5 Gbps (Euro)DOCSIS 3.0 262 Mbps (theoretical, 8 x 32.78 Mbps)
■ Channel bandwidth	DOCSIS 3.1 max. 96 MHz (Euro)DOCSIS 3.0 200, 400, 800 kHz 1.6, 3.2 and 6.4 MHz
■ Output impedance	75 Ohm

MoCA (optional)

- Bonded MoCA 2.0
- Full backward compatibility to MoCA 1.1
- Support for up to 16 MoCA network nodes
- Throughput up to 800 Mbps
- Expanded range of operating frequencies – 1150 MHz to 1650 MHz
- Supports both parameterized and prioritized QoS

Wi-Fi

- Full dual-band concurrent Wi-Fi radios, Wi-Fi certified®
3x3 Wi-Fi 6 (IEEE 802.11ax) 2.4 GHz access point
4x4 Wi-Fi 6 (IEEE 802.11ax) 5 GHz access point
- Wi-Fi power levels adopted to meet requirements per regulatory region
- Wi-Fi security levels WPA3™-Enterprise / WPA2™-Enterprise / WPA™-Enterprise
WPA3™-Personal / WPA2™-Personal / WPA™-Personal
WPA3™ + WPA2™ + WPA™ mixed mode (SAE, AES and TKIP)
IEEE802.1x port-based authentication with RADIUS client
- Wi-Fi Protected Setup (WPS™)
- Wi-Fi Multimedia (WMM®) and WMM-Power Save
- Up to 8 BSSIDs (virtual AP) support per radio interface
- Wi-Fi hotspot capabilities Airtime Fairness
Client Isolation
- Band Steering
- Zero-Wait DFS
- Explicit and Implicit Beamforming
- Multi-User MIMO
- Dynamic rates switching for optimal wireless rates
- Manual/ auto radiochannel selection

Voice and telephony

- | | |
|----------------------|--------------------------------------------------------------------------------------------------------------------|
| ■ Voice technologies | Voice over IP (VoIP) |
| ■ Voice signalling | (Euro)PacketCable™ NCS
Network-based call signalling protocol (PKT-SP-EC-MGCP)
RFC 3261 SIP
RFC 2805 MGCP |

Management

- Customizable user-friendly GUI via HTTP
- Web-based user interface management and administration
- Command Line Interface (CLI)
Telnet
SSH v2
- TR-069 CPE WAN Management Protocol (CWMP)
- SNMP
SNMP v1, SNMP v2, SNMP v3
- Operation, Administration & Maintenance (OAM)
ITU-T Y.1731
- Software upgrade via WAN RF connection only
- Zero-touch autoprovisioning

Package contents

- MARLIN L CGA4236
- Power supply unit
- Ethernet cable
- Quick Setup leaflet(s) (optional)
- Safety Instructions & Regulatory Information

TECHNICOLOR DELIVERY TECHNOLOGIES

8-10 rue du Renard, 75004 Paris, France

www.technicolor.com

SALES CONTACT

For more information please get in touch with your usual sales representative or use the following email:

contactsales@technicolor.com

