

ARRIS BSR64000

CARRIER CMTS/EDGE ROUTER PLATFORM

High-density, fully redundant Cable Modem Termination System (CMTS)/intelligent edge router that allows broadband operators to rapidly introduce differentiated data, voice, and multimedia services for both corporate and residential subscribers. It also offers the robust routing, flexibility, and scalability required to support the emerging generation of revenue-generating services, such as Voice over IP (VoIP) and Virtual Private Networks (VPNs). For the BSR64k concept downstream and upstream modules (TX/RX32) are available.



- Fully redundant, carrier-class system architected for "nines" (99.999 percent) availability
- Based on open system standards, the BSR 64000 is Docsis 3.0 Bronze Qualified and EuroDocsis 2.0 qualified, PacketCable 1.1 qualified and PacketCable Multimedia (PCMM) qualified
- Advanced Spectrum Management featuring an integrated, intelligent spectrum analyzer ensures reliable and highquality service delivery, and enables efficient migration to Docsis 2.0
- Carrier-class intradomain, interdomain, and multicast routing with OSPF v2, RIP v1 and v2, BGP4, IS-IS, VRRP, IGMP, IP Tunneling, DVMRP, and PIM-SM.
- SmartFlow QoS classification for thousands of flows at wirespeed with guaranteed SLA
- Virtual Private Networking and open access support with policy-based routing and full-featured MPLS Carrier-class reliability and robust QoS control enables support for realtime VoIP services

SPECIFICATIONS

CARRIER-CLASS CHASSIS
Hot-swappable modules with redundancy High availability architecture: 1:1 SRM redundancy, 1:N 2:8 Euro/DOCSIS Module redundancy, 1:2 TX32 Euro/DOCSIS, 1:1 High-Speed Interface Module redundancy, Redundant power and fan units, Integrated RF switch Advanced real-time operating systems such as VxWorks and INTEGRITY provide high levels of reliability, availability, and security for the BSR 64000
STANDARDS-BASED INTEROPERABILITY
DOCSIS 2.0 and EuroDOCSIS 2.0 qualified DOCSIS 3.0 and EuroDOCSIS 3.0 bronze qualified PacketCable 1.1 and EuroPacket Cable 1.0 qualified PacketCable Multimedia 1.0 and EuroPacket Cable 1.0 qualified
FLEXIBLE CAPACITY CONFIGURATIONS
Flexible downstream capacity expansion with the TX32 Decoupled Downstream I-CMTS Module Ether-Flex Card offers two ports of Gigabit Ethernet with SFP optics or eight ports of 10/100 Fast Ethernet
ROUTING
Internet Protocol version 4 and version 6 (IPv4 and IPv6) Open Shortest Path First Version 2 (OSPFv2) Border Gateway Protocol version 4 (BGPv4) Multiprotocol Label Switching (MPLS) Routing Information Protocol (RIP) version 1 and 2 Static Routes Intermediate System-to-Intermediate System (IS-IS) BGP/MPLS VPNs Virtual Router Redundancy Protocol (VRRP)
MULTICAST
Internet Group Management Protocol (IGMP) version 1, 2, and 3 Protocol Independent Multicast-Sparse Mode (PIM-SM) Protocol Independent Multicast-Source Specific Multicast (PIM-SSM)
IP ADDRESS MANAGEMENT
DHCP Relay

TRAFFIC MANAGEMENT

Marking, policing and shaping
Two-level class-based scheduling
SmartFlow™ per-flow queuing
Longest Queue Pushout (LQP) congestion management

SECURITY MANAGEMENT

IPSec Tunnels
MD5 Authentication
BPI+
Cable and Lawful Intercept

HIGH-PERFORMANCE IP ROUTING

Hardware-based forwarding and flow classification
Routing policy support
More than 3 million PPS for each High-Speed Interface Module
More than 42 million PPS for each chassis

ADVANCED QOS

Hardware-based wire-speed QoS
IP DiffServ, standards-based MPLS, BGP/MPLS VPNs (RFC 2547), per-SID queuing

PACKETIZED VOICE SERVICE SUPPORT

Dynamic QoS (DQoS)
Common Open Policy Service (COPS)
IPSec

LOGGING AND MONITORING

Syslog
Traceroute and Ping (IPv4 and IPv6)

SYSTEM-MANAGEMENT AND PROVISIONING

Management and diagnostic capabilities:
SSH, TACACS/TACACS+, and RADIUS
10/100BASE-T port for management
SNMP v1/v2/v3
Telnet with security extensions
DOCSIS, IETF and Arris MIBs
Multiple levels of account/password authentication
Open interfaces for provisioning, accounting and billing applications

PHYSICAL

Form: 16-slot, 17 RU, NEBS-compliant chassis
Dimensions: 29.75 in H x 19.75 in W x 19.75 in D (75.56 cm x 48.26 cm x 50.17 cm)
Fully configured weight: 140 lbs (63.5 kgs)

POWER

Input power: -48 VDC
Optional Tyco NP1200 AC to DC Carrier-Class Power Converter

STANDARDS-BASED INTEROPERABILITY

DOCSIS 3.0 Downstream channel bonding capable
DOCSIS 2.0 A-TDMA, S-CDMA and LOGICAL CHANNEL QUALIFIED
Integrated downstream RF upconverters
2:8 Advanced Spectrum Management

DOWNSTREAM RF

Downstream modulation: 64 and 256 QAM
Downstream frequency range (fc): DOCSIS 91-870(999*)MHz
EuroDOCSIS 112-869 (998*)MHz
Frequency step: 32.0 kHz
Downstream per-channel bit rates:
DOCSIS 27-38Mbps
EuroDOCSIS 36-56Mbps
RF output level: 44-60 dBmV
Bandwidth:
DOCSIS 6 MHz
EuroDOCSIS Up to 8 MHz
Modulation Error Rate (MER): 47 Typ ica I
Output load impedance: 75 W

UPSTREAM RF

Upstream frequency range:
DOCSIS 5-42 MHz
J-DOCSIS 5-55 MHz
EuroDOCSIS 5-65 MHz
Upstream modulation: QPSK, 16, 32, 64, 128, and 256 QAM
Upstream per-channel bit rate: 0.320 - 40.96 Mbps
Input load impedance: 75 W

AVAILABLE RF MODULES

2:8 Line Card, 2.0 (Euro)Docsis, 2 Downstreams/8 Upstreams
TX32 (Euro)Docsis Downstream 3.0 Card – 32 Downstreams (8 RF Ports) – active/redundant Version
TXPLUS (Euro)Docsis 3.0 Card – 48 Downstreams (8 RF Ports) – active/redundant Version
RX48 (Euro)Docsis Upstream 3.0 Card – 48 Upstreams/QAM Receivers (8 RF Ports) – active/redundant Version
SRM4 – System Resource Module - active/redundant Version
ETHERFLEX – Network Interface Module (2x GbE und 8x 10/100 Base-T)
SRM10 – System Resource Module & Network Interface - active/redundant Version