

Type	V 912-ASI		V 912-ASI CI
Order number	380 923		380 926
EAN-Code	4026187611095		4026187131593
<b>ASI input</b>			
Connectors		MCX-jacks, 75	
Data rate	[MBit/s]	270	
Transmission modes		Packet burst / continuous	
Packet length		188, 204	
<b>COFDM modulator</b>			
Modulation		QPSK; 16 QAM; 64 QAM	
Signal processing		according DIN EN 300744	
Transmission modes		2k (8k on request)	
Coding rates		1/2; 2/3; 3/4; 5/6; 6/7; 7/8	
Bandwidth	[MHz]	6, 7 or 8	
<b>TS editing</b>			
Data rate adjustment			<input checked="" type="checkbox"/>
PCR correction			<input checked="" type="checkbox"/>
NIT handling			<input checked="" type="checkbox"/>
PID filtering and remapping			<input checked="" type="checkbox"/>
Service filtering		Pass- / Drop-Filter	
<b>HF output</b>			
channel selective filter pluggable			<input checked="" type="checkbox"/>
Connectors	[Ω]	IEC-jack, 75	
Frequency range	[MHz]	47 - 862 (K2 - K69) in 0,1 MHz-steps adjustable	
Output level	[dBμV]	80...96, adjustable	
MER	[dB]	typ. 36	
Spurious frequency distance 40 - 862 MHz > 950 MHz	[dB]	> 60 discrete interferences / > 57 noise interferences > 20 according to 100 dBμV system level and 90 dBμV operation level	
<b>Common data</b>			
Power consumption	[W]	10,0	11,6
Ambient temperature	[°C]	0...+50	