

## DVB-ASI output module for Luminato platform

The DVB-ASI output module enables flexible multiplexing of SPTS and MPTS video services and also PSI/SI table streams. High quality multiplexing module is ideal for an IP centric headend to create MPTS at the main headend for sending through DVB-ASI or IP network to remote headends.



### Versatile functionality

Luminato multiplexer enables flexible multiplexing of SPTS and MPTS video services and also PSI/SI table streams. The multiplexer is ideal for an IP centric headend to create MPTS at the main headend and send them through to IP network to remote headends.

The Luminato quad ASI output module support selection of free-to-air and scrambled services from IP stream sources, which can be adjusted to the operator's service line-up with the built-in advanced transport stream processing capabilities. The Luminato quad ASI output module support Standard Definition, High Definition and 3D video in MPEG-2 and MPEG-4 AVC video formats and numerous audio formats.

### Effective flexibility

Luminato quad ASI output module is fully compatible with the high-

performance Luminato chassis, where it can be fitted freely to any of the six module slots. In accordance with the Luminato system architecture, the video processing is performed on the quad ASI output modules, which enables low-cost applications even with partially equipped chassis, while having the performance scalability to fully equipped chassis.


### Embedded content protection

Quad QAM module has the optional capability to do DVB Common Scrambling Algorithm content protection. The embedded scrambling doesn't require any additional hardware and the user can freely select which services will be scrambled. The component level scrambling is also supported to allow only video and audio scrambling and leave other streams untouched to avoid descrambling challenges for bursty data in set-top box.

### Efficiency and reliability

With the advanced transport stream processing, operator can select the services and components which are relevant to his network. The Luminato will follow-up any changes on the stream to automatically readjust the processing to provide uninterrupted service. This will allow the operator to efficiently manage network capacity usage.

The available tools provide high degree of automated features to minimise the cost of system set-up and operation, and avoiding downtime due to changes in the received services.



Block Diagram, Quad ASI Out

## Features

- DVB TS over UDP/IP or RTP/UDP/IP reception
- IP address / UDP port selector for input streams
- Network dejittering
- Support CBR and VBR TS
- Advanced transport stream processing
- Supports SPTS and MPTS multiplexing
- PCR processing
- Automatic PSI/SI table generation
- Custom PSI/SI table creation and streaming
- DVB CSA content protection (LAS-D)
- MPEG transport stream over UDP/IP and RTP/UDP/IP streaming
- MPTS passthrough
- DVB-ASI output
- Multiplex IP streaming (VBR or CBR)

## Technical specifications

| Parameter   | Specification      | Note                       | Parameter   | Specification        | Note                  |
|---|--------------------|----------------------------|---|----------------------|-----------------------|
| <b>IP inputs</b>  |                    |                            | <b>IP streamer output of multiplexer</b>                              |                      |                       |
| Frame formats   | UDP/IP, RTP/UDP/IP |                            | Framing format  | UDP/IP, RTP/UDP/IP   |                       |
| TS packets per UDP frame                                  | 1 ... 7            |                            | Traffic type  | unicast or multicast |                       |
| Max inputs streams per module                             | 120                |                            | TS format   | VBR, CBR             |                       |
| Dejittering buffersize                                    | 200 ms             |                            | Max TS speed per streamer   | 75 Mb/s              |                       |
| <b>Multiplexers</b>                                       |                    |                            | Maximum speed total   | 250 Mb/s             | shared with 4 outputs |
| Number of multiplexer per module                          | 4                  |                            | <b>General</b>  |                      |                       |
| Max input services per multiplexer                        | 120                |                            | Power consumption   | 6,5 W                |                       |
| Max input services per module                             | 120                |                            | Supply voltages   | 24 V                 |                       |
| Max components per service                                | 32                 |                            | Connectors, DVB ASI out   | BNC 75 ohm           |                       |
| <b>DVB Common Scrambling Algorithm Content Protection</b> |                    |                            | Dimensions  | 20 x 109 x 253 mm    | (HxWxD), 1)           |
| Max scrambled services per module                         | 120                | LAS-D                      | Weight  | 0,3 kg               |                       |
| <b>DBV ASI Output</b>                                     |                    |                            | Enclosure classification  | IP21                 |                       |
| Impedance   | 75 ohm             |                            | Operating temperature range   | -10...+55 °C         |                       |
| Traffic mode  | adjustable         | variable/constant bit rate | Storage temperature range   | -30...+70 °C         |                       |
| Output speed for constant bitrate                         | adjustable         | 1...75 Mb/s                | Specification is met  | 0...+45 °C           |                       |
| Maximum speed per interface                               | 75 Mb/s            | payload traffic            | <b>Note!</b><br>1) Dimensions excluding connectors and locking screws |                      |                       |
| Maximum speed total (4 ports)                             | 250 Mb/s           | shared with 4 outputs      |   |                      |                       |
| Standard  | EN 50083-9         |                            |   |                      |                       |