

ARRIS GX2 CM100B

CONTROLLER MODULE

- Power PC technology provided by Arris for enhanced intelligence
- Internal subagent allows communication with SNMP and requires no proprietary software
- Provides quick swap capabilities where replacement modules are recognized and updated with the prestored set-tings
- Downloadable firmware
- Two ethernet ports for communication with local PC and standard network management system
- Hot swappable with blind mating to OmniStar GX2 housing
- Contact closure relay for external alarm capability



Communications interface	
Local Ethernet Port (front panel)	
Data format	SNMP
Data rate	10 Mbit/s (10 BaseT Ethernet)
Connector	RJ-45
Network Management Port (rear panel)	
Data format	SNMP
Data rate	10 Mbit/s (10 BaseT Ethernet)
Connector	RJ-45
Shelf display unit connector	Mini-DIN
Alarm Relay	Contact Closure, 250 mA/40 VAC or VDC Max
General data	
Power consumption	Max. 5 Watt
Operating temperature range	- 20° ... + 65°C
Storage temperature range	- 40° ... + 80°C
Dimensions	2,5 x 15 x 38 cm
Weight	1 kg
Mounting	GX2-HSG* Chassis / Equipment shelf

Model	Description
GX2-CM100B	Controller Modul / Control Module