

ASTRO HFD 111 / 212

2- / 4-WAY TAPS



TYPE		HFD 111			HFD 212		
Frequency range	[MHz]	5...2400					
THROUGH LOSS							
5-40 MHz	[dB]	10,5			10,5		
40-1000 MHz	[dB]	10,5			11		
1000-2050 MHz	[dB]	12			11,5		
2050-2400 MHz	[dB]	13,5			13		
INSERTION LOSS							
5-40 MHz	[dB]	2,5			3,5		
40-1000 MHz	[dB]	1,5			2,5		
1000-2050 MHz	[dB]	3,0			4,5		
2050-2400 MHz	[dB]	4,0			5,5		
DECOUPLING ATTENUATION							
		Stamm			Stamm		Stamm
5-40 MHz	[dB]	10,5			17		15
40-1000 MHz	[dB]	10,5			25		30
1000-2050 MHz	[dB]	12			20		25
2050-2400 MHz	[dB]	13,5			15		20
RETURN LOSS							
		Input	Output	Stich	Input	Output	Stich
5-40 MHz	[dB]	11	13	5	8	13	5
40-1000 MHz	[dB]	14	12	14	14	12	13
1000-2050 MHz	[dB]	14	10	14	15	10	12
2050-2400 MHz	[dB]	8	10	10	8	10	10
COMMON DATA							
Connections	[dB]	F-Connectors					
Shielding		Class A acc. EN 50083-2					
Impedance	[Ω]	75					