



ALPHA  
OUTBACK  
ENERGY

# Power

## APX2L-Linear

LINEAR NON-STANDBY-POWER-SUPPLY 63V 15A / 20A / 30A

### APX2L-Linear

Linear Non Standby Power supply

Cable TV Power supply

#### Input :

Highly efficient advanced linear design

Input voltage: 230Vac 50Hz , 6A max input Intensity

Breaker: 6A Type C

Lightening protection with control

Cable input with cable gland

Separated ground terminal (M6) linked to the frame

#### Output:

Output Power 63 Vac sine wave with one 54Vac output

15A/20A/30A full output intensity

4 fuse (6.3-32) protected 63 Vac outputs with cable

1 fuse (6.3-32) protected 54 Vac output with cable

**The full intensity consumed on the 5 outputs must not exceed 20 A/30A at the risk of the transformer being destroyed**

#### Options:

Metal Cover / Digital Amp Meter

#### *Mechanical characteristics:*

*Aluminium connector board Thickness 2mm  
Height. 350mm Width 277mm Depth 170mm  
Mounting holes: Height 250mm Width 242mm  
Gross weight: 22,6kg – Net weight: 21,7kg*

#### Worldwide Corporate Offices

##### Headquarter Germany

Hansastraße 8  
D-91126 Schwabach  
Tel: +49 9122 79889 0  
Fax: +49 9122 79889 21  
Mail: [info@alpha-outback-energy.com](mailto:info@alpha-outback-energy.com)

##### Eastern Europe

[ee@alpha-outback-energy.com](mailto:ee@alpha-outback-energy.com)

##### France and Benelux

[fbnl@alpha-outback-energy.com](mailto:fbnl@alpha-outback-energy.com)

##### Africa

[africa@alpha-outback-energy.com](mailto:africa@alpha-outback-energy.com)

##### Middle East

[me@alpha-outback-energy.com](mailto:me@alpha-outback-energy.com)

##### Spain

[spain@alpha-outback-energy.com](mailto:spain@alpha-outback-energy.com)

Alpha and Outback Energy GmbH reserves the right to make changes to the products and information contained in this document without notice. Copyright © 2020 Alpha and Outback Energy GmbH. All Rights reserved.

For more information, please visit [www.alpha-outback-energy.com](http://www.alpha-outback-energy.com)

